The RC65 filler returns a compact and well distributed soil: mainly suited for the filling of trays, pots and containers in general which must then be sown.

The soil is distributed by a 4-blade rotor with adjustable speed: this is used to easily adjust the final density of the soil in the cells.


The machine is robust, simple to use and easy to maintain. Particularly suitable for production lines that require the changeover of the filling material during operation: the emptying of the hopper and the complete cleaning of the components, in fact, are quick and simple to perform, thus saving operator time.

It is equipped with cranks for quick self-centring adjustment of the contaners. Excess soil recovery belt available as an accessory.


Thanks to the feeding belt system, the RC65 filler can be used both as a stand-alone machine and in a working line.








p. 64-65





- Double chain soil elevator.
- **2** Easily usable soil loading height.
- **3** Soil distribution with 4-blade longitudinal rotor, electronically controlled.

## TECHNICAL SPECIFICATIONS

- Quick self-centring guide adjustment system.
- **4** Double auger spillway with motorized brush for tray cleaning.
- **5** Electric control panel start-stop, emergency and limit switch.
- Available in left and right version.

TECHNICAL DATA	M.U.	RC65	RC65 A	RC65 E
HOURLY PRODUCTION (max)	trays/hour	600	600	600
HOPPER CAPACITY (standard)	I	700 (*)	700 (*)	700 (*)
TRAYS DIMENSIONS (max)	mm	600x400	750x400	750x500
TRAYS HEIGHT (max)	mm	200	200	200
INSTALLED POWER	kW	4,5	4,5	4,5
WEIGHT	kg	585	585	585



(\*)= hopper capacity 550 liters if combined with recovery excess soil belt (ACCESSORY)

# - up to 600 trays/hour



# **MAIN ACCESSORIES**




Electropneumatic 3-movements destacker, for thermoformed trays

47 PE - PET.



### **AVAILABLE ON:**

RN12, RT12, RE14, RC65



Feed belt for single trays or empty stacks for destacker L = 3300/4300/5300/6300 mm.



### AVAILABLE ON:

RN12, RT12, RE14, RC65



Electropneumatic destaker with **2-movements**, adjustable with a single crank; for polystyrene trays and trays holder.



RN12, RT12, RE14, RC65



**Destacker** for heavy plastic trays at injection in polypropylene PP.



### AVAILABLE ON:

RN12, RT12, RE14, RC65

- Advancement belt with electronically adjustable speed from 200 to 800 trays/hour.
- **Soil compactor** with rotating movement and eccentric for **adjustable density**.
- Device for hopper emptying with frequency driver.
- Soil hopper extension with additional capacity of 500 liters.

**AVAILABLE ON:** RT12


• Vibrating table on conveyor belt.

AVAILABLE ON: RN12, RT12, RE14, RC65





Acceleration belt
530 mm at the outlet
for the connection
to other machines.



Fixed table positioned at tray filler exit.



Belt system for the exceeding soil recycle.



Quick self-centring guides adjustment system.

**AVAILABLE ON:** RN12, RT12, RE14, RC65

**AVAILABLE ON:** RC65, RE14

**AVAILABLE ON:** RC65, RE14

AVAILABLE ON:



55


Hopper 900 liters.



Hopper 1000 liters, complete with bulkhead and nr. 2 turning wheels.



Adjustment device for trays with legs.



Motorized exit roller, with nr. 4 rows.



RN12, RC65, RT12

Wheels kit for handling.

**AVAILABLE ON:** RN12, RT12

**AVAILABLE ON:** RC65, RE14

**AVAILABLE ON:** RN12, RC65, RE14

AVAILABLE ON:
ALL TRAY FILLER

**AVAILABLE ON:** RC65, RE14

